

6 October 1999

P53821C

Applicant: Richard G. Hyatt Jr.

Serial No.: 08/720,070

Filed: 27 September 1996

For: ELECTROMECHANICAL CYLINDER PLUG

Document filed:

1. Fee Transmittal/check(s) of \$399.00 (#33823)
2. Third Supplemental Amendment



COPY

# FEE TRANSMITTAL

Patent fees are subject to annual revision on October 1.  
These are the fees effective October 1, 1997.  
Small Entity payments must be supported by a small entity statement,  
otherwise large entity fees must be paid. See Forms PTO/SB/09-12.  
See 37 C.F.R. §§1.27 and 1.28.

## Complete If Known

Application Number	08/726,070
Filing Date	27 September 1996
First Named Inventor	Richard G. Hyatt Jr.
Examiner Name	Boucher, D.
Group/Art Unit	3627
Attorney Docket No.	P53821C

TOTAL AMOUNT OF PAYMENT

(\$)399.00

## METHOD OF PAYMENT (check one)

1. ☐ The Commissioner is hereby authorized to charge indicated fees and credit any over payments to:

Deposit Account Number: 02-4943  
Deposit Account Number: \_\_\_\_\_

☐ Charge Any Additional Fee Required Under 37 C.F.R. §1.16 and 1.17. ☐ Charge the Issue Fee Set in 37 C.F.R. §1.18 at the Mailing of the Notice of Allowance.

## 2. ☒ Payment Enclosed: (CHECK #33823)

☒ Check ☐ Money Order ☐ Other

## FEE CALCULATION (continued)

### 3. ADDITIONAL FEES

Large Entity		Small Entity		Fee Description	Fee Paid
Fee Code	Fee (\$)	Fee Code	Fee (\$)		
105	130	205	65	Surcharge-late filing fee or oath	\$
127	50	227	25	Surcharge-late provisional filing fee or cover sheet	\$
139	130	139	130	Non-English specification	\$
147	2,520	147	2,520	For filing a request for reexamination	\$
112	920*	112	920*	Requesting publication of SIR prior to Examiner action	\$
113	1,840*	113	1,840*	Requesting publication of SIR after Examiner action	\$
115	110	215	55	Extension for reply within first month	\$
116	380	216	190	Extension for reply within second month	\$
117	870	217	435	Extension for reply within third month	\$
118	1,360	218	680	Extension for reply within fourth month	\$
128	1,850	228	925	Extension for reply within fifth month	\$
119	300	219	150	Notice of Appeal	\$
120	300	220	150	Filing a brief in support of an appeal	\$
121	260	221	130	Request for oral hearing	\$
138	1,510	138	1,510	Petition to institute a public use proceeding	\$
140	110	240	55	Petition to revive - unavoidable	\$
141	1,210	241	605	Petition to revive - unintentional	\$
142	1,210	242	605	Utility issue fee (or reissue)	\$
143	430	243	215	Design issue fee	\$
144	580	244	290	Plant issue fee	\$
122	130	122	130	Petitions to the Commissioner	\$
123	50	123	50	Petitions related to provisional applications	\$
126	240	126	240	Submission of Information Disclosure Statement	\$
581	40	581	40	Recording each patent assignment per property (Times number of properties)	\$
146	760	246	380	Filing a submission after final rejection (37 C.F.R. §1.129(a))	\$
149	760	249	380	For each additional invention to be examined (37 C.F.R. §1.129(b))	\$
Other Fee (specify) _____					
Other Fee (specify) _____					

## FEE CALCULATION

### 1. BASIC FILING FEE

Large Entity		Small Entity		Fee Description	Fee Paid
Fee Code	Fee (\$)	Fee Code	Fee (\$)		
101	760	201	380	Utility filing fee	\$
106	310	206	155	Design filing fee	\$
107	480	207	240	Plant filing fee	\$
108	760	208	380	Reissue filing fee	\$
114	150	214	75	Provisional filing fee	\$
SUBTOTAL (1)					(\$) <u>0.00</u>

### 2. EXTRA CLAIM FEES

		Extra Claims		Fee from below	Fee Paid
Total claims	-20** =	14	x	9	= 126
Independent Claims	-3** =	7	x	39	= 273

Multiple Dependent =

\*\* or number previously paid, if greater; For Reissues, see below

### Large Entity Small Entity

Fee Code	Fee (\$)	Fee Code	Fee (\$)	Fee Description	
103	18	203	9	Claims in excess of 20	
102	78	202	39	Independent claims in excess of 3	
104	260	204	130	Multiple dependent claim, if not paid	
109	78	209	39	** Reissue independent claims over original patent	
110	18	210	9	** Reissue claims in excess of 20 and over original patent	

SUBTOTAL (2) (\$)399.00

\*\* Reduced by Basic Filing Fee Paid

SUBTOTAL (3) \$0.00

## SUBMITTED BY

## Complete (if applicable)

Typed or Printed Name	Robert E. Bushnell, Esq.		Reg. Number	27,774
Signature	Date	6 October 1999	Deposit Account	

COPY

ROBERT E. BUSHNELL

33823

LAW OFFICES  
1522 K STREET, N.W., SUITE 300  
WASHINGTON, D.C. 20005-1202  
(202) 638-5740

CITIBANK F.S.B.  
WASHINGTON, D.C. 20036-0967  
1570142540

10/6/1999

PAY TO THE ORDER OF U.S. Department of Treasury

\$ \*\*399.00

Three Hundred Ninety-Nine and 00/100\*\*\*\*\*

DOLLARS

Assistant Commissioner  
of Patent  
Washington, D.C. 20231  
Box: PROSECUTION

*X This is a copy.  
Do not cash this.*

COPY

MEMO

Serial No. 08/720,070/extra claim coverag

0033823 254070116 6678 4867

ROBERT E. BUSHNELL

33823

COPY

ROBERT E. BUSHNELL

33823

COPY

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Richard G. Hyatt Jr.

Serial No.: 08/720,070 (CPA application) Examiner: BOUCHER, D.

Filed: 27 September 1996 Art Unit: 3627

For: ELECTROMECHANICAL CYLINDER PLUG

AMENDMENT

Assistant Commissioner  
for Patents  
Washington, D.C. 20231

Sir:

Entry of the following amendments, re-consideration and re-examination are applied to Paper

No. 25, an Office action dated 17 August 1999.

Folio: P53821C  
Date: 10/06/99  
I.D.: REB/mf

COPY

**IN THE CLAIMS**

Please cancel Claims 60 through 63, amend Claims 25, 39, 43, 46 and 56, and add Claims 64 through 77, as follows:

1           25. (Thrice Amended) A lock, comprising:

2                   a shell containing a hollow recess defining a longitudinal axis and an interior  
3           cylindrical surface;

4                   a cylinder plug rotatable around said longitudinal axis while resident within said  
5           hollow recess;

6                   a bar interposed between said shell and said cylinder plug to reciprocate generally  
7           along a radial plane between a first position engaging both said shell and said plug while obstructing  
8           rotation of said cylinder plug within said recess, and a second position accommodating said rotation,  
9           said cylinder plug comprising:

10                   a first base and a second base separated by an axial length of said cylinder plug from  
11           said first base, said second base bearing means for supporting a cam; and

12                   an electrical operator borne by said cylinder plug and rotatable with said cylinder  
13           plug, said electrical operator being electrically operable to respond to a control signal by moving  
14           between a first orientation and a second and different orientation providing obstruction of said bar.

1           39. (Amended) The lock of claim 25, further comprising:

2                   a [basic] logic circuit generating said control signal in response to a comparison

3 between a code set within said logic circuit and a [date] data signal applied to said logic circuit;  
4 a conductor provided by said plug, conveying said data signal to said logic circuit;  
5 and  
6 said electrical operator moving between said second orientation and said first  
7 orientation in response to said control signal.

1 43. (Amended) A lock, comprising:

2 a cylinder containing a hollow interior recess defining a longitudinal axis, and bearing  
3 a slot within said recess; and

4 a plug rotatable from a rest orientation around said longitudinal axis while resident  
5 within said hollow recess relative to said cylinder; and

6 an elongate member positioned between said cylinder and plug while extending into  
7 said slot, and providing simultaneous engagement of said cylinder and said plug while said plug  
8 remains in said rest orientation;

9 said plug comprising:

10 a first base bearing an orifice spaced-apart from and separated by a mass of  
11 said plug from said keyway;

12 a second base separated by an axial length of said plug from said first base,  
13 said second base disposed to support a cam, said mass being penetrated by a radially oriented  
14 aperture;

15 an exterior surface extending between said first base and said second base;

16 a conductor having a terminal exposed to an exterior of said first base through  
17 said orifice;

18 an electronic logic circuit comprising a memory storing a code, said circuit  
19 being borne by said plug and coupled to receive data signals via said conductor, said circuit  
20 generating control signals in dependence upon a comparison between said code and  
21 information borne by said data signal; [and]

22 an electrical operator mounted within said aperture, said operator having a  
23 movable member [travelling] traveling in dependence upon said control signals between a  
24 first position relative to said exterior surface maintaining said simultaneous engagement and  
25 a second and different position relative to said exterior surface accommodating movement  
26 between said plug and said cylinder; and

27 a component biasing said movable member to maintain said simultaneous  
28 engagement.

1 46. (Amended) A lock, comprising:

2 a shell containing a hollow recess defining a longitudinal axis and an interior  
3 cylindrical surface;

4 a cylinder plug rotatable around said longitudinal axis while resident within said  
5 hollow recess;

6 a bar borne by said plug and rotatable with said plug relative to said shell, said bar  
7 being interposed between said shell and said cylinder plug to reciprocate generally along a radial

8 plane between a first position engaging both said shell and said cylinder plug while obstructing  
9 rotation of said cylinder plug within said recess, and a second position accommodating said rotation,  
10 said cylinder plug comprising:

11 a first base and a second base separated by an axial length of said plug from said first  
12 base, said second base bearing means for supporting a cam; and

13 an electrical operator being electrically operable to respond to an electrical control  
14 signal by moving obstructing movement of said bar between said first position and said second  
15 position in response to a first state of said control signal and [accommodating] moving within a  
16 second and different plane not coextensive with said radial plane in response to application of said  
17 control signal to accommodate said movement of said bar in response to a second and different state  
18 of said control signal.

1 56. (Amended) A lock, comprising:

2 a shell containing a hollow recess defining a longitudinal axis and an interior  
3 cylindrical surface;

4 a plug rotatable around said longitudinal axis while resident within said hollow  
5 recess;

6 an elongate member interposed between said shell and said plug to travel generally  
7 along a radial direction between a first position engaging both said shell and said plug while  
8 obstructing rotation of said plug within said recess, and a second position accommodating said  
9 rotation;

10 said plug comprising:

11 a first base perforated by an aperture, and a second base separated by an axial  
12 length of said plug from said first base, said second base bearing means for supporting a  
13 cam;

14 a logic circuit borne by said plug and rotatable with said plug, conveying said  
15 data signal between said aperture to said logic circuit; and

16 an electrical operator responding to said control signals by moving in a second  
17 direction not aligned with said radial direction between a first orientation obstructing said  
18 travel and relative operable movement between said shell and said plug while said electrical  
19 operator is contained wholly within said plug, and a second and different orientation  
20 accommodating said travel and said relative operable movement between said shell and said  
21 plug.

1 --64. A lock, comprising:

2 a shell containing a hollow recess defining a longitudinal axis and an interior  
3 cylindrical surface;

4 a cylinder plug rotatable around said longitudinal axis while resident within said  
5 hollow recess, said cylinder plug comprising a first base and a second base separated by an axial  
6 length of said cylinder plug from said first base, said second base bearing means for supporting a  
7 cam;

8 a bar interposed between said shell and said cylinder plug to travel generally along

a radial plane between a first position engaging both said shell and said plug while obstructing rotation of said cylinder plug within said recess, and a second position accommodating said rotation;

a logic circuit generating an electrical control signal in response to a comparison between a code set within said logic circuit and a data signal applied to said logic circuit;

an electrical conductor provided by said plug, conveying said data signal to said logic circuit; and

an electrical operator borne by said cylinder plug and rotatable with said plug, said electrical operator being electrically operable to respond to said control signal by moving between a first orientation providing obstruction of said travel and a second and different accommodating said travel.

--65. A lock, comprising:

a shell containing a hollow recess defining a longitudinal axis and an interior cylindrical surface;

a cylinder plug rotatable around said longitudinal axis while resident within said hollow recess, said cylinder plug comprising a first base and a second base separated by an axial length of said cylinder plug from said first base, said second base bearing means for supporting a cam;

a bar interposed between said shell and said cylinder plug to travel generally along a radial plane between a first position engaging both said shell and said plug while obstructing rotation of said cylinder plug within said recess, and a second position accommodating said rotation;

11 a logic circuit generating a control signal in response to a comparison between a code  
12 set within said logic circuit and a data signal applied to said logic circuit;

13 an electrical conductor provided by said plug, conveying said data signal to said logic  
14 circuit; and

15 an electrical operator comprising an armature, said armature being borne by said  
16 cylinder plug and rotating around said longitudinal axis with said plug, said electrical operator being  
17 electrically operable to respond to said control signal by moving between a first orientation  
18 providing obstruction of said travel and a second and different orientation accommodating said  
19 travel.

1 --66. The lock of claim 65, with said electrical operator further comprising a coil of an  
2 electrically conducting material that is borne by said cylinder plug and wound to drive said armature  
3 to move from one of said first and second orientations to the other of said first and second  
4 orientations in response to said control signal.

1 --67. The lock of claim 65, with said electrical operator further comprising a coil of an  
2 electrically conducting material that is borne by said cylinder plug and wound to drive said armature  
3 to move from said first orientation to said second orientation in response to said control signal.

4 --68. The lock of claim 65, with electrical operator further comprising a coil of an  
5 electrically conducting material that is borne by said cylinder plug and wound to drive said armature

6 to rotate around an arc in response to said control signal.

1 --69. The lock of claim 65, with said electrical operator further comprising a coil of an  
2 electrically conducting material that is borne by said cylinder plug and wound to drive said armature  
3 to reciprocate along a radial axis that is transverse to said radial plane in response to said control  
4 signal.

1 --70. A lock, comprising:

2 a shell containing a hollow recess defining a longitudinal axis and an interior  
3 cylindrical surface;

4 a cylinder plug rotatable around said longitudinal axis while resident within said  
5 hollow recess, said cylinder plug comprising a first base and a second base separated by an axial  
6 length of said cylinder plug from said first base, said second base bearing means for supporting a  
7 cam;

8 a bar interposed between said shell and said cylinder plug to travel generally along  
9 a radial plane between a first position engaging both said shell and said plug while obstructing  
10 rotation of said cylinder plug within said recess, and a second position accommodating said rotation;

11 a logical circuit generating said control signal in response to a comparison between  
12 a code set within said logic circuit and a data signal applied to said logic circuit;

13 an electrical conductor provided by said plug, conveying said data signal to said logic  
14 circuit; and

15 an electrical operator borne by said cylinder plug and rotatable with said plug, said  
16 electrical operator being electrically operable to respond to an electrical control signal applied to said  
17 electrical operator by moving along a geometrical construct other than to said radial plane between  
18 a first orientation providing obstruction of said travel and a second and different orientation  
19 accommodating said travel.

1 --71. The lock of claim 70, with said electrical operator further comprising an armature and  
2 a coil of an electrically conducting material that is borne by said cylinder plug and wound to drive  
3 said armature to move along said geometric construct in response to said control signal.

1 --72. The lock of claim 70, with said electrical operator further comprising an armature and  
2 a coil of an electrically conducting material that is borne by said cylinder plug and wound to drive  
3 said armature to move along said geometric construct in response to said control signal from said  
4 second orientation to said first orientation.

5 --73. The lock of claim 70, with said geometric construct comprising an arc and said  
6 electrical operator further comprising an armature and a coil of an electrically conducting material  
7 that is borne by said cylinder plug and wound to drive said armature to rotate around said arc in  
8 response to said control signal.

1 --74. The lock of claim 70, with said geometric construct comprising a radial axis that is

transverse to said radial plane, and said electrical operator further comprising an armature and a coil of an electrically conducting material that is borne by said cylinder plug and wound to drive said armature to reciprocate along said radial axis in response to said control signal.

--75. A lock, comprising:

a shell containing a hollow recess defining a longitudinal axis and an interior cylindrical surface;

a cylinder plug rotatable around said longitudinal axis while resident within said hollow recess, said cylinder plug comprising a first base and a second base separated by an axial length of said cylinder plug from said first base, said second base bearing means for supporting a cam;

a bar interposed between said shell and said cylinder plug to travel generally along a radial plane between a first position engaging both said shell and said plug while obstructing rotation of said cylinder plug within said recess, and a second position accommodating said rotation;

a logic circuit generating said control signal in response to a comparison between a code set within said logic circuit and a data signal applied to said logic circuit;

an electrical conductor provided by said plug, conveying said data signal to said logic circuit; and

an electrical operator borne by said cylinder plug and rotatable with said plug, said electrical operator being electrically operable to respond to said control signal by moving along a radial axis that is transverse to said radial plane, between a first orientation providing obstruction of

18 said travel and a second and different orientation accommodating said travel.

1 --76. A lock, comprising:

2 a shell containing a hollow recess defining a longitudinal axis and an interior  
3 cylindrical surface;

4 a cylinder plug rotatable around said longitudinal axis while resident within said  
5 hollow recess, said cylinder plug comprising a first base and a second base separated by an axial  
6 length of said cylinder plug from said first base, said second base bearing means for supporting a  
7 cam;

8 a logic circuit generating said control signal in response to a comparison between a  
9 code set within said logic circuit and a data signal applied to said logic circuit;

10 an electrical conductor provided by said plug, conveying said data signal to said logic  
11 circuit;

12 an elongate bar exhibiting a greatest longitudinal dimension along a second axis that  
13 extends transversely to said first base and to said second base, said bar being interposed between said  
14 shell and said cylinder plug to travel generally along a radial axis that is transverse to said second  
15 axis, between a first position engaging both said shell and said plug while obstructing rotation of said  
16 cylinder plug within said recess, and a second position accommodating said rotation; and

17 an electrical operator borne by said cylinder plug and rotatable with said plug, said  
18 electrical operator being electrically operable to respond to said control signal by moving along said  
19 radial axis between a first orientation providing obstruction of said travel and a second and different

20 orientation accommodating said travel.

1 --77. A lock, comprising:

2 a shell containing a hollow recess defining a longitudinal axis and an interior  
3 cylindrical surface;

4 a cylinder plug rotatable around said longitudinal axis while resident within said  
5 hollow recess, said cylinder plug comprising a first base and a second base separated by an axial  
6 length of said cylinder plug from said first base, said second base bearing means for supporting a  
7 cam;

8 a logic circuit generating said control signal in response to a comparison between a  
9 code set within said logic circuit and a data signal applied to said logic circuit;

10 an electrical conductor provided by said plug, conveying said data signal to said logic  
11 circuit;

12 an elongate bar exhibiting a greatest longitudinal dimension along a second axis that  
13 extends transversely to said first base and to said second base, said bar being interposed between said  
14 shell and said cylinder plug to travel generally along a radial axis that is radial to said cylinder plug  
15 and transverse to said second axis, between a first position engaging both said shell and said plug  
16 while obstructing rotation of said cylinder plug within said recess, and a second position  
17 accommodating said rotation; and

18 an electrical operator borne by said cylinder plug and rotatable with said plug, said  
19 electrical operator being electrically operable to respond to a control signal by moving between a

20 first orientation providing obstruction of said travel and a second and different orientation  
21 accommodating said travel.

1 --78. The lock of claim 25, with said electrical operator further comprising an armature and  
2 a coil of an electrically conducting material that is borne by said cylinder plug and wound to drive  
3 said armature to move from one of said first and second orientations to the other of said first and  
4 second orientations in response to said control signal.

1 --79. The lock of claim 25, with said electrical operator further comprising an armature and  
2 a coil of an electrically conducting material that is borne by said cylinder plug and wound to drive  
3 said armature to move from said first orientation to said second orientation in response to said  
4 control signal.

1 --80. The lock of claim 25, with electrical operator further comprising an armature and a  
2 coil of an electrically conducting material that is borne by said cylinder plug and wound to drive said  
3 armature to rotate around an arc in response to said control signal.

1 --81. The lock of claim 25, with said electrical operator further comprising an armature and  
2 a coil of an electrically conducting material that is borne by said cylinder plug and wound to drive  
3 said armature to reciprocate along a radial axis that is transverse to said radial plane in response to  
said control signal.

REMARKS

Claims 1 through 59 and 64 through 81 are pending; claims 25, 39, 43, 46 and 56 are amended while claims 64 through 81 are newly presented.

Non-elected claims 60 through 63 have been canceled and are presented in a divisional application, together with a request for interference.

Amended claims 39, 43, 46 and 56, together with newly added claims 64 through 81, define, among other things, the elected species of Figs. 8A through 8G. The Applicant notes that the Examiner had asserted that claims 43 through 45 were withdrawn from consideration; Applicant notes however, that claims 43 and 44 clearly define the elected species, while claim 45 depends upon the more generic parent independent claim 43. Accordingly, claims 43 and 44 must be considered.

Claims 25 through 31, 39 through 42, 46 through 52, 54 and 56 were alternatively rejected under 35 U.S.C. §102(e) as anticipated by or under 35 U.S.C. §103(a) rendered obvious by Gokcebay U.S. 5,552,777. Applicant traverses this rejection for the following reasons.

Each of these claims, together with newly presented claims 64 through 81, define, *"inter alia,"* a "bar" interpose between a shell and a cylinder plug, and an "electrical operator". As defined by claim 25, for example, the electrical operator is "electrically operable to respond to a control

signal by moving ... ." In contradistinction, Gokcebay '777 uses a spring 48 that does not, respond to either a control signal or to any electrical stimulus by moving. The Examiner's attention is directed to the transitive and intransitive sense of the verb "move". In effect, the Examiner is re-writing Applicant's claims to substitute "by being *moved* between" for the express language currently used by these claims of "by *moving* between." This is an impermissible interpretation of Applicant's claims. In both mechanical and electrical analogues, the spring is considered as a passive, rather than an active component; consequently, the spring does not move itself, and must be moved by some external force. Applicant's electrical operator is defined by these claims as "being electrically operable to respond ... by *moving* between ... ." These distinctions are significant because they provide Applicant with indirect, rather than direct locking, and a concomitant increase in mechanical advantage to the user of components such as a side bar or detent. These features are utterly lacking from the art represented by Gokcebay '777.

Moreover, the Examiner's interpretation of Gokcebay '777 to identify his spring 48 as something that is "considered electrically operable" is improper, and contrary to the express teachings of Gokcebay '777. In claim 1 of Gokcebay '777, by way of the example, lines 10 through 14 define the spring while lines 21 through 26 define the operator. These components are distinct, serve distinct functions and cannot be twisted, in their meaning, like a nose made of wax, in order to improperly read these components upon Applicant's language.

Even assuming *arguendo* that the Gokcebay '777 blocking pin/armature item 38 is a "bar"

instead of an armature and blocking pin, the Examiner's interpretation still has overlooked how the lock of Gokcebay '777 works and how that is different from the pending claims. According to Gokcebay '777, the "compression spring" item 48 is described in "Description of Preferred Embodiments" in Section 6 line 43 as follows: "The small solenoid 36 when powered overcomes the force of the compression spring 48. In section 8, line 21, it reads "When the solenoid is powered the blocking pin 38 will be released ie: retracted, and the operator [a human person] will be able to rotate the key in the lock, since the key bittings will match the bittings in the lock." Line 26 reads "the master ie: the microprocessor 72 sends the unique number again to U1 to turn off U2 and Q1, stopping the current to the solenoid and allowing the compression spring to *push the blocking pin outwardly* when the cylinder plug is returned to the locked position".

Of course the Gokcebay drawings illustrate the blocking pin/armature as being one in the same, with the spring constituting merely a spring.

If the Examiner believes that the "electrical operator" of the pending claims might be read as the spring of Gokcebay '777 and that the blocking pin of Gokcebay '777 could be read as a "bar" or sidebar, then Gokcebay<sup>15</sup> spring does not provide "obstruction of said bar" as defined by Applicant's claims because, in fact, the spring provides no obstruction. It does exactly what Gokcebay describes, by biasing the blocking pin outwardly in the same manner as any biasing element, it intrinsically lacks the structure and is inherently devoid of the capacity to "obstruct" the "bar" simply because the same spring must freely and continuously, even in the absence of Applicant's control signal,


allow full reciprocation of the blocking pin of Gokcebay '777. Spring 48 of Gokcebay '777 is neither able to both concurrently and simultaneously "respond to" Applicant's control signal, provide Applicant's "obstruction of said bar," or be "electrically operable". Consequently, spring 48 cannot be considered to "be electrically operable" as asserted by the Examiner in support of this rejection. Moreover, if spring 48 were "electrically operable to move ...," then solenoid 36 of Gokcebay '777 would have no function. In short, the Examiner must consider "the subject matter" of each of these claims "as whole" in conformance with the requirement of §103, and must recognize that determinations of obviousness require an evaluation of all of the elements of each claim. The Examiner cannot accurately assert that "spring 48" of Gokcebay '777 has all of the characteristics and attributes of "blocking pin 38" of Gokcebay '777 without impermissibly requiring the solenoid 36 and spring 48 to function in a mode that is contrary to the express teachings of Gokcebay '777.

In view of the foregoing distinctions, and the advantageous results flowing therefrom, withdrawal of these rejections and allowance of claims 25 through 33, 39 through 56, and newly added claims 64 through 81 is required.

A fee of \$399.00 (**SMALL ENTITY**) is incurred by fourteen (14) extra claims and seven (7) extra independent claims. The check of Applicant's attorney drawn to pay to the order of Commissioner of this amount, is enclosed. Should the check become lost, should other fees be incurred, the Commissioner is authorized to charge Deposit Account No. 02-4943 of Applicant's undersigned attorney in the amount of such fees.

In view of the foregoing amendments and remarks, all claims are deemed to be in condition for allowance. Entry of these amendments, withdrawal of the single outstanding art rejection and passage of this application to issue is respectfully requested. Should questions remain unresolved however, the Examiner is requested to telephone Applicant's undersigned attorney.

Respectfully submitted,

  
Robert E. Bushnell,  
Attorney for the Applicant  
Registration No.: 27,774

1522 "K" Street N.W., Suite 300  
Washington, D.C. 20005-1202  
(202) 638-5740

Folio: P53821C  
Date: 10/6/99  
I.D.: REB/mf